INTERNATIONAL STANDARD

First edition 2010-11-01

Safety of machinery — General principles for design — Risk assessment and risk reduction

Sécurité des machines — Principes généraux de conception — Appréciation du risque et réduction du risque



Reference number ISO 12100:2010(E)

This is a preview. Click here to purchase the full publication.

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Contents

Forewo	ord	v
Introductionvi		
1	Scope	1
2	Normative references	1
-	Torme and definitions	
3	Terms and definitions	1
4	Strategy for risk assessment and risk reduction	9
5	Risk assessment	12
5.1	General	12
5.Z	Information for risk assessment.	12
5.3 5.2.1	General	13
5.3.1	General	13
533	Snare limits	14
534	Time limits	14
535	Other limits	14
5.4	Hazard identification	14
5.5	Risk estimation	16
5.5.1	General	16
5.5.2	Elements of risk	17
5.5.3	Aspects to be considered during risk estimation	19
5.6	Risk evaluation	21
5.6.1	General	21
5.6.2	Adequate risk reduction	21
5.6.3	Comparison of risks	21
6	Risk reduction	22
6.1	General	22
6.2	Inherently safe design measures	23
6.2.1	General	23
6.2.2	Consideration of geometrical factors and physical aspects	23
6.2.3	Taking into account general technical knowledge of machine design	24
6.2.4	Choice of appropriate technology	25
6.2.5	Applying principle of positive mechanical action	25
6.2.6	Provisions for stability	25
6.2.7	Provisions for maintainability	26
6.2.8	Observing ergonomic principles	26
6.2.9	Electrical hazards	27
6.2.10	Pneumatic and hydraulic hazards	27
6.2.11	Applying inherently safe design measures to control systems	28
6.2.12	Minimizing probability of failure of safety functions	33
6.2.13	Limiting exposure to hazards through reliability of equipment	33
6.2.14	Limiting exposure to nazards through mechanization or automation of loading (feeding)/	~ 4
6745	Limiting exposure to begarde through leastion of patting and maintenance paints autoide	54
0.2.13	danger zones	21
63	Safaquarding and complementary protective measures	34
631	Ganaral	34
632	Selection and implementation of quards and protective devices	35
633	Requirements for design of guards and protective devices	<u>4</u> 0
6.34	Safeguarding to reduce emissions	43
~. ~. ~		

6.3.5	Complementary protective measures	44
6.4	Information for use	46
6.4.1	General requirements	46
6.4.2	Location and nature of information for use	46
6.4.3	Signals and warning devices	46
6.4.4	Markings, signs (pictograms) and written warnings	47
6.4.5	Accompanying documents (in particular — instruction handbook)	48
7	Documentation of risk assessment and risk reduction	51
Annex	A (informative) Schematic representation of a machine	52
Annex	B (informative) Examples of hazards, hazardous situations and hazardous events	53
Annex	C (informative) Trilingual lookup and index of specific terms and expressions used in ISO 12100	63
Bibliog	raphy	75

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12100 was prepared by Technical Committee ISO/TC 199, Safety of machinery.

This first edition of ISO 12100 cancels and replaces ISO 12100-1:2003, ISO 12100-2:2003 and ISO 14121-1:2007, of which it constitutes a consolidation without technical change. It also incorporates the Amendments ISO 12100-1:2003/Amd.1:2009 and ISO 12100-2:2003/Amd.1:2009. Documentation (e.g. risk assessment, type-C standards) based on these replaced documents need not be updated or revised.

Introduction

The primary purpose of this International Standard is to provide designers with an overall framework and guidance for decisions during the development of machinery to enable them to design machines that are safe for their intended use. It also provides a strategy for standards developers and will assist in the preparation of consistent and appropriate type-B and type-C standards.

The concept of safety of machinery considers the ability of a machine to perform its intended function(s) during its life cycle where risk has been adequately reduced.

This International Standard is the basis for a set of standards which has the following structure:

- type-A standards (basic safety standards) giving basic concepts, principles for design and general aspects that can be applied to machinery;
- type-B standards (generic safety standards) dealing with one safety aspect or one type of safeguard that can be used across a wide range of machinery:
 - type-B1 standards on particular safety aspects (for example, safety distances, surface temperature, noise);
 - type-B2 standards on safeguards (for example, two-hand controls, interlocking devices, pressuresensitive devices, guards);
- type-C standards (machine safety standards) dealing with detailed safety requirements for a particular machine or group of machines.

This International Standard is a type-A standard.

When a type-C standard deviates from one or more technical provisions dealt with by this International Standard or by a type-B standard, the type-C standard takes precedence.

It is desirable that this International Standard be referred to in training courses and manuals to convey basic terminology and general design methods to designers.

ISO/IEC Guide 51 has been taken into account as far as practicable at the time of drafting of this International Standard.

Safety of machinery — General principles for design — Risk assessment and risk reduction

1 Scope

This International Standard specifies basic terminology, principles and a methodology for achieving safety in the design of machinery. It specifies principles of risk assessment and risk reduction to help designers in achieving this objective. These principles are based on knowledge and experience of the design, use, incidents, accidents and risks associated with machinery. Procedures are described for identifying hazards and estimating and evaluating risks during relevant phases of the machine life cycle, and for the elimination of hazards or the provision of sufficient risk reduction. Guidance is given on the documentation and verification of the risk assessment and risk reduction process.

This International Standard is also intended to be used as a basis for the preparation of type-B or type-C safety standards.

It does not deal with risk and/or damage to domestic animals, property or the environment.

NOTE 1 Annex B gives, in separate tables, examples of hazards, hazardous situations and hazardous events, in order to clarify these concepts and assist the designer in the process of hazard identification.

NOTE 2 The practical use of a number of methods for each stage of risk assessment is described in ISO/TR 14121-2.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60204-1:2005, Safety of machinery — Electrical equipment of machines — Part 1: General requirements

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

machinery

machine

assembly, fitted with or intended to be fitted with a drive system consisting of linked parts or components, at least one of which moves, and which are joined together for a specific application

NOTE 1 The term "machinery" also covers an assembly of machines which, in order to achieve the same end, are arranged and controlled so that they function as an integral whole.

NOTE 2 Annex A provides a general schematic representation of a machine.

© ISO 2010 – All right

3.2

reliability

ability of a machine or its components or equipment to perform a required function under specified conditions and for a given period of time without failing

3.3

maintainability

ability of a machine to be maintained in a state which enables it to fulfil its function under conditions of intended use, or to be restored to such a state, with the necessary actions (maintenance) being carried out according to specified practices and using specified means

3.4

usability

ability of a machine to be easily used owing to, among others, properties or characteristics that enable its function(s) to be easily understood

3.5

harm

physical injury or damage to health

3.6

hazard

potential source of harm

NOTE 1 The term "hazard" can be qualified in order to define its origin (for example, mechanical hazard, electrical hazard) or the nature of the potential harm (for example, electric shock hazard, cutting hazard, toxic hazard, fire hazard).

NOTE 2 The hazard envisaged by this definition either

- is permanently present during the intended use of the machine (for example, motion of hazardous moving elements, electric arc during a welding phase, unhealthy posture, noise emission, high temperature), or
- can appear unexpectedly (for example, explosion, crushing hazard as a consequence of an unintended/unexpected start-up, ejection as a consequence of a breakage, fall as a consequence of acceleration/deceleration).

NOTE 3 The French term "*phénomène dangereux*" should not be confused with the term "*risque*", which was sometimes used instead in the past.

3.7

relevant hazard

hazard which is identified as being present at, or associated with, the machine

NOTE 1 A relevant hazard is identified as the result of one step of the process described in Clause 5.

NOTE 2 This term is included as basic terminology for type-B and type-C standards.

3.8

significant hazard

hazard which has been identified as relevant and which requires specific action by the designer to eliminate or to reduce the risk according to the risk assessment

NOTE This term is included as basic terminology for type-B and type-C standards.

3.9

hazardous event

event that can cause harm

NOTE A hazardous event can occur over a short period of time or over an extended period of time.

3.10

hazardous situation

circumstance in which a person is exposed to at least one hazard

NOTE The exposure can result in harm immediately or over a period of time.

3.11

hazard zone

danger zone

any space within and/or around machinery in which a person can be exposed to a hazard

3.12

risk

combination of the probability of occurrence of harm and the severity of that harm

3.13

residual risk

risk remaining after protective measures have been implemented

NOTE 1 This International Standard distinguishes

— the residual risk after protective measures have been implemented by the designer,

the residual risk remaining after all protective measures have been implemented.

NOTE 2 See also Figure 2.

3.14

risk estimation

defining likely severity of harm and probability of its occurrence

3.15

risk analysis

combination of the specification of the limits of the machine, hazard identification and risk estimation

3.16

risk evaluation

judgment, on the basis of risk analysis, of whether the risk reduction objectives have been achieved

3.17

risk assessment

overall process comprising a risk analysis and a risk evaluation

3.18

adequate risk reduction

risk reduction that is at least in accordance with legal requirements, taking into consideration the current state of the art

NOTE Criteria for determining when adequate risk reduction is achieved are given in 5.6.2.

3.19

protective measure

measure intended to achieve risk reduction, implemented

- by the designer (inherently safe design, safeguarding and complementary protective measures, information for use) and/or
- by the user (organization: safe working procedures, supervision, permit-to-work systems; provision and use of additional safeguards; use of personal protective equipment; training)

NOTE See Figure 2.

© ISO 2010 – All right

This is a preview. Click here to purchase the full publication.