



JAPANESE
INDUSTRIAL
STANDARD

Translated and Published by
Japanese Standards Association

JIS T 8024

(JSAA/JSA)

**Clothing for protection against heat
and flame — Determination of heat
transmission on exposure to both
flame and radiant heat**

ICS 13.340.10

Reference number : JIS T 8024 : 2009 (E)

Date of Establishment: 2009-07-25

Date of Public Notice in Official Gazette: 2009-07-27

Investigated by: Japanese Industrial Standards Committee
Standards Board
Technical Committee on Protective Equipment
for Occupational Safety

JIS T 8024: 2009, First English edition published in 2009-11

Translated and published by: Japanese Standards Association
4-1-24, Akasaka, Minato-ku, Tokyo, 107-8440 JAPAN

In the event of any doubts arising as to the contents,
the original JIS is to be the final authority.

© JSA 2009

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

Printed in Japan

MT

Contents

	Page
Introduction	1
1 Scope	2
2 Normative references	3
3 Terms and definitions.....	4
4 Principle.....	6
5 Apparatus	7
5.1 General	7
5.2 Thermal-flux source.....	8
5.3 Specimen holding support	8
5.4 Protective shutter	9
5.5 Specimen mounting plate	9
5.6 Specimen holding plate.....	9
5.7 Spacer	9
5.8 Sensor assembly	9
5.9 Recorder.....	11
5.10 Gas supply	11
5.11 Gas rotameter.....	11
5.12 Radiometer	11
5.13 Solvent.....	11
6 Precautions	11
7 Sampling.....	11
7.1 Specimen dimensions.....	12
7.2 Number of specimens.....	12
8 Conditioning and testing atmospheres	12
8.1 Conditioning atmosphere.....	12
8.2 Testing atmosphere	12
9 Test procedure	12
9.1 Calibration procedures	12
9.2 Sensor care	14
9.3 Specimen holder care.....	14
9.4 Preparation of heat transfer/burn intersection overlay.....	15
9.5 Test specimen mounting.....	15
9.6 Test-specimen exposure.....	15
10 Expression of results	16
10.1 Selection of analysis method.....	16