

NFPA[®]

68

Standard on Explosion Protection by Deflagration Venting

2018



This is a preview. [Click here to purchase the full publication.](#)

IMPORTANT NOTICES AND DISCLAIMERS CONCERNING NFPA® STANDARDS

NOTICE AND DISCLAIMER OF LIABILITY CONCERNING THE USE OF NFPA STANDARDS

NFPA® codes, standards, recommended practices, and guides (“NFPA Standards”), of which the document contained herein is one, are developed through a consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on fire and other safety issues. While the NFPA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy of any information or the soundness of any judgments contained in NFPA Standards.

The NFPA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on NFPA Standards. The NFPA also makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

In issuing and making NFPA Standards available, the NFPA is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the NFPA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The NFPA has no power, nor does it undertake, to police or enforce compliance with the contents of NFPA Standards. Nor does the NFPA list, certify, test, or inspect products, designs, or installations for compliance with this document. Any certification or other statement of compliance with the requirements of this document shall not be attributable to the NFPA and is solely the responsibility of the certifier or maker of the statement.

REVISION SYMBOLS IDENTIFYING CHANGES FROM THE PREVIOUS EDITION

Text revisions are shaded. A **Δ** before a section number indicates that words within that section were deleted and a **Δ** to the left of a table or figure number indicates a revision to an existing table or figure. When a chapter was heavily revised, the entire chapter is marked throughout with the **Δ** symbol. Where one or more sections were deleted, a **•** is placed between the remaining sections. Chapters, annexes, sections, figures, and tables that are new are indicated with an **N**.

Note that these indicators are a guide. Rearrangement of sections may not be captured in the markup, but users can view complete revision details in the First and Second Draft Reports located in the archived revision information section of each code at www.nfpa.org/docinfo. Any subsequent changes from the NFPA Technical Meeting, Tentative Interim Amendments, and Errata are also located there.

ALERT: THIS STANDARD HAS BEEN MODIFIED BY A TIA OR ERRATA

Users of NFPA codes, standards, recommended practices, and guides (“NFPA Standards”) should be aware that NFPA Standards may be amended from time to time through the issuance of a Tentative Interim Amendment (TIA) or corrected by Errata. An official NFPA Standard at any point in time consists of the current edition of the document together with any TIAs and Errata then in effect.

To determine whether an NFPA Standard has been amended through the issuance of Tentative Interim Amendments or corrected by Errata, go to www.nfpa.org/docinfo to choose from the list of NFPA Standards or use the search feature to select the NFPA Standard number (e.g., NFPA 13). The document information page provides up-to-date document-specific information as well as postings of all existing TIAs and Errata. It also includes the option to register for an “Alert” feature to receive an automatic email notification when new updates and other information are posted regarding the document.

IMPORTANT NOTICES AND DISCLAIMERS CONCERNING NFPA® STANDARDS

ADDITIONAL NOTICES AND DISCLAIMERS

Updating of NFPA Standards

Users of NFPA codes, standards, recommended practices, and guides (“NFPA Standards”) should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of Tentative Interim Amendments or corrected by Errata. An official NFPA Standard at any point in time consists of the current edition of the document together with any Tentative Interim Amendments and any Errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of Tentative Interim Amendments or corrected through the issuance of Errata, consult appropriate NFPA publications such as the National Fire Codes® Subscription Service, visit the NFPA website at www.nfpa.org, or contact the NFPA at the address listed below.

Interpretations of NFPA Standards

A statement, written or oral, that is not processed in accordance with Section 6 of the Regulations Governing the Development of NFPA Standards shall not be considered the official position of NFPA or any of its Committees and shall not be considered to be, nor be relied upon as, a Formal Interpretation.

Patents

The NFPA does not take any position with respect to the validity of any patent rights referenced in, related to, or asserted in connection with an NFPA Standard. The users of NFPA Standards bear the sole responsibility for determining the validity of any such patent rights, as well as the risk of infringement of such rights, and the NFPA disclaims liability for the infringement of any patent resulting from the use of or reliance on NFPA Standards.

NFPA adheres to the policy of the American National Standards Institute (ANSI) regarding the inclusion of patents in American National Standards (“the ANSI Patent Policy”), and hereby gives the following notice pursuant to that policy:

NOTICE: The user’s attention is called to the possibility that compliance with an NFPA Standard may require use of an invention covered by patent rights. NFPA takes no position as to the validity of any such patent rights or as to whether such patent rights constitute or include essential patent claims under the ANSI Patent Policy. If, in connection with the ANSI Patent Policy, a patent holder has filed a statement of willingness to grant licenses under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license, copies of such filed statements can be obtained, on request, from NFPA. For further information, contact the NFPA at the address listed below.

Law and Regulations

Users of NFPA Standards should consult applicable federal, state, and local laws and regulations. NFPA does not, by the publication of its codes, standards, recommended practices, and guides, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

NFPA Standards are copyrighted. They are made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of safe practices and methods. By making these documents available for use and adoption by public authorities and private users, the NFPA does not waive any rights in copyright to these documents.

Use of NFPA Standards for regulatory purposes should be accomplished through adoption by reference. The term “adoption by reference” means the citing of title, edition, and publishing information only. Any deletions, additions, and changes desired by the adopting authority should be noted separately in the adopting instrument. In order to assist NFPA in following the uses made of its documents, adopting authorities are requested to notify the NFPA (Attention: Secretary, Standards Council) in writing of such use. For technical assistance and questions concerning adoption of NFPA Standards, contact NFPA at the address below.

For Further Information

All questions or other communications relating to NFPA Standards and all requests for information on NFPA procedures governing its codes and standards development process, including information on the procedures for requesting Formal Interpretations, for proposing Tentative Interim Amendments, and for proposing revisions to NFPA standards during regular revision cycles, should be sent to NFPA headquarters, addressed to the attention of the Secretary, Standards Council, NFPA, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101; email: stds_admin@nfpa.org.

For more information about NFPA, visit the NFPA website at www.nfpa.org. All NFPA codes and standards can be viewed at no cost at www.nfpa.org/docinfo.

Copyright © 2017 National Fire Protection Association®. All Rights Reserved.

NFPA® 68

Standard on

Explosion Protection by Deflagration Venting

2018 Edition

This edition of NFPA 68, *Standard on Explosion Protection by Deflagration Venting*, was prepared by the Technical Committee on Explosion Protection Systems. It was issued by the Standards Council on November 10, 2017, with an effective date of November 30, 2017, and supersedes all previous editions.

This document has been amended by one or more Tentative Interim Amendments (TIAs) and/or Errata. See "Codes & Standards" at www.nfpa.org for more information.

This edition of NFPA 68 was approved as an American National Standard on November 30, 2017.

Origin and Development of NFPA 68

NFPA 68, *Standard on Explosion Protection by Deflagration Venting*, started out as a tentative standard in 1945, titled NFPA 68T, *Explosion Venting Standard*. In 1954, the temporary standard was replaced with NFPA 68, *Guide for Explosion Venting*, which brought together all the best available information on the fundamentals and parameters of explosions, the data developed by small-scale tests, the interpretation of the results of those tests, and the use of vents and vent closures that were current at the time. The information was then related to "rules of thumb" vent ratio recommendations, which were used for many years. Some of the vents that were designed using those rules of thumb functioned well, while others were never put to the test.

Beginning in 1954, extensive experimentation was carried out in Great Britain and Germany and added to the existing information. The U.S. Bureau of Mines also did some work in this area. However, the work was not completed because the group involved was reassigned to different programs.

In 1974, NFPA 68 was revised, and the work done in Great Britain and Germany was included with the hope that the new information would provide a means for calculating vent ratios with a greater degree of accuracy than that provided by the rules of thumb. The 1978 revision included substantial data that were more valuable in designing explosion relief vents.

In 1979, the committee began a major effort to rewrite the guide in order to incorporate the results of the test work done in Germany. In addition, the 1988 edition, titled *Guide for Venting of Deflagrations*, contained rewritten text that more clearly explained the various parameters that affect the venting of deflagrations.

The 1994 edition of NFPA 68 was completely rewritten to more clearly explain the principles of venting deflagrations. Revisions to each chapter improved the organization of information within the document without changing the venting methodology. The thrust of this revision was to improve the user friendliness and adoptability of the guide and to clarify this complex technology.

The 1998 edition introduced updated terminology to be consistent with current industrial practice. New information was added on the effects of vent ducts, calculation methods for evaluating those effects, and the effects of vent discharge. The revision also incorporated the "weak roof-to-shell" joint design as a means of venting silos and bins and provided new information on explosions in elongated vessels. It also clarified the provisions for securing restraint panels.

The 2002 edition represented a complete revision of the guide and included updated and enhanced treatment for deflagration venting design for dusts and hybrid mixtures. The revision also included new vent design equations based upon the methodology developed by Factory Mutual Research Corporation. In addition to the generalized correlation for dusts were new methods to evaluate the effects of vent ducts, partial volumes, vent panel inertia, and initially elevated pressures.

All design guidelines for gas mixtures were combined into a single chapter, and the document was revised in accordance with the NFPA *Manual of Style for NFPA Technical Committee Documents*.

The 2007 edition represented a complete revision, including a change from guide to standard. The new standard, titled *Standard on Explosion Protection by Deflagration Venting*, provided mandatory requirements for the design, location, installation, maintenance, and use of devices and systems to vent combustion gases and pressures from deflagrations.

The Committee incorporated a new chapter on performance-based design that enabled users to present alternative design methods to satisfy the requirements for gas and mist mixtures, for dusts, and for hybrid mixtures. The Committee also revised the generalized correlation for dusts on the basis of a review of additional experimental data. That review enabled the Committee to support revisions to the basic equation, along with changes to the equations for low-inertia vent closures, panel inertia, partial volume, initially elevated pressures, and vent ducts. The Committee also added a new chapter on inspection and maintenance.

The 2013 edition introduced a revised calculation method for venting of deflagrations of gas mixtures. The chapter on venting of deflagrations in dust mixtures was revised to address differences between translating vent panels and hinged vent panels, to permit sub atmospheric initial pressures, and to incorporate new research on the entrainment of accumulated dust in a building. New sections addressed bucket elevators and grain silos, and new annex material provided guidance on designing vent ducts and estimating the fundamental burning velocity of a fuel.

In the 2018 edition, a requirement has been added to adjust the K_{St} values for certain metal dusts if the K_{St} value was obtained in a vessel smaller than 1 m³, and an equation has been added to determine the hydraulic diameter for rectangular enclosures. The chapter on venting gas mixture and mist deflagrations was reorganized to clarify the order and applicability of the various adjustments and corrections to required vent area, and a new annex was added to implement the equations and calculation procedures, including partial volume effects. The requirements for determining K_G were replaced with requirements for determining P_{max} , and the equations to determine the turbulent flame enhancement factor were revised.

The chapter on venting dust and hybrid mixture deflagrations was also reorganized in order of intended execution. The equation for determining vent area for elevated or subatmospheric pressure was revised, and an example calculation was added to the annex. The method of determining enclosure volume for dust collectors was revised, and a definition for *flexible filter* has been added. Requirements for the use of plastic buckets in bucket elevators have been moved from the annex to the body of the standard.

Technical Committee on Explosion Protection Systems

Larry D. Floyd, *Chair*
BASF, AL [U]

Luke S. Morrison, *Secretary*
Professional Loss Control Inc., Canada [SE]

C. Regis Bauwens, FM Global, MA [I]
Rep. FM Global

Venkateswara Sarma Bhamidipati, Powder Process Solutions, MN [IM]

Martin P. Clouthier, JENSEN HUGHES, Canada [SE]

William V. F. Cosey, Savannah River Nuclear Solutions, LLC, SC [U]

Michael Davies, PROTEGO, Germany [M]

Randal R. Davis, IEP Technologies/HOERBIGER, MA [M]

Nathan R. Egbert, Schenck Process LLC, MO [SE]

Henry L. Febo, Jr., Holliston, MA [SE]

Robert J. Feldkamp, Nordson Corporation, OH [M]

Richard G. Fredenburg, State of North Carolina, NC [E]
Rep. International Fire Marshals Association

Dan A. Guaricci, ATEX Explosion Protection, L.P., FL [M]

Michael D. Hard, Hard Fire Suppression Systems, Inc., OH [M]
Rep. Fire Suppression Systems Association

Manuel Herce, E. I. DuPont de Nemours & Company, DE [U]

Alfonso F. Ibarreta, Exponent, Inc., MA [SE]

Steven A. McCoy, Ingredion, IN [U]
Rep. NFPA Industrial Fire Protection Section

Scott W. Ostrowski, ExxonMobil Research and Engineering, TX [U]

Rep. American Petroleum Institute

Stefan Penno, Rembe GmbH Safety & Control, Germany [M]

Samuel A. Rodgers, Honeywell, Inc., VA [U]

Mitchel L. Rooker, BS&B Safety Systems, LLC, OK [M]

Cleveland B. Skinker, Bechtel Infrastructure and Power Corporation, VA [SE]

Bill Stevenson, CV Technology, Inc., FL [M]

David R. Stottmann, ST Storage, KS [M]

Jérôme R. Taveau, Fike Corporation, MO [M]

James Kelly Thomas, Baker Engineering & Risk Consultants, Inc., TX [SE]

David E. Trull, Global Asset Protection Services, LLC, WA [I]

Erdem A. Ural, Loss Prevention Science & Technologies, Inc., MA [SE]

Robert G. Zalosh, Firexplo, MA [SE]

Alternates

Geof Brazier, BS&B Safety Systems, LLC, OK [M]
(Alt. to Mitchel L. Rooker)

Todd A. Dillon, Global Asset Protection Services, LLC, OH [I]
(Alt. to David E. Trull)

Thomas Heidermann, Braunschweiger Flammenfilter G, Germany [M]
(Alt. to Michael Davies)

Kirk W. Humbrecht, Phoenix Fire Systems, Inc., IL [M]
(Alt. to Michael D. Hard)

Edward L. Jones, Nordson Corporation, OH [M]
(Alt. to Robert J. Feldkamp)

David C. Kirby, Baker Engineering & Risk Consultants, Inc., WV [SE]
(Alt. to James Kelly Thomas)

Jason Krbec, CV Technology, Inc., FL [M]
(Alt. to Bill Stevenson)

John A. LeBlanc, FM Global, MA [I]
(Alt. to C. Regis Bauwens)

Gerd Ph. Mayer, Rembe, Inc., NC [M]
(Alt. to Stefan Penno)

Keith McGuire, CST Storage, KS [M]
(Alt. to David R. Stottmann)

Timothy J. Myers, Exponent, Inc., MA [SE]
(Alt. to Alfonso F. Ibarreta)

David M. Nieman, Bechtel Corporation, VA [SE]
(Alt. to Cleveland B. Skinker)

Alvin Grant Roach, Professional Loss Control Inc., Canada [SE]
(Alt. to Luke S. Morrison)

Thomas C. Scherpa, DuPont, NH [U]
(Alt. to Manuel Herce)

Jef Snoeys, Fike Corporation, Belgium [M]
(Alt. to Jérôme R. Taveau)

Nonvoting

Laurence G. Britton, Process Safety Consultant, WV [SE]

Vladimir Molkov, University of Ulster, Northern Ireland, UK [SE]

Laura E. Moreno, NFPA Staff Liaison

This list represents the membership at the time the Committee was balloted on the final text of this edition. Since that time, changes in the membership may have occurred. A key to classifications is found at the back of the document.

NOTE: Membership on a committee shall not in and of itself constitute an endorsement of the Association or any document developed by the committee on which the member serves.

Committee Scope: This Committee shall have primary responsibility for documents on explosion protection systems for all types of equipment and for buildings, except pressure venting devices designed to protect against overpressure of vessels such as those containing flammable liquids, liquefied gases, and compressed gases under fire exposure conditions, as now covered in existing NFPA standards.

Contents

Chapter 1 Administration	68- 5	8.10 Venting Internal to a Building with Flame-Arresting and Particulate Retention Device.	68- 26
1.1 Scope.	68- 5	8.11 Venting Silos or Other Storage Vessel Provided with Integral Bin Vents.	68- 26
1.2 Purpose.	68- 5	8.12 Deflagration Venting of Enclosures Interconnected with Pipelines.	68- 27
1.3 Application.	68- 5		
1.4 Retroactivity.	68- 5	Chapter 9 Venting of Deflagrations of Gases and Dusts in Pipes and Ducts Operating at or Near Atmospheric Pressure	68- 27
1.5 Equivalency.	68- 5	9.1 Introduction.	68- 27
1.6 Conversion Factors.	68- 5	9.2 Design.	68- 27
1.7 Symbols.	68- 6	9.3 Multiple Deflagration Vents on a Pipe or Duct.	68- 28
1.8 Pressure.	68- 6		
Chapter 2 Referenced Publications	68- 6	Chapter 10 Details of Deflagration Vents and Vent Closures	68- 29
2.1 General.	68- 6	10.1 Normally Open Vents.	68- 29
2.2 NFPA Publications.	68- 6	10.2 Normally Closed Vents.	68- 29
2.3 Other Publications.	68- 7	10.3 Types of Building or Room Vent Closures.	68- 29
2.4 References for Extracts in Mandatory Sections.	68- 7	10.4 Restraints for Large Panels.	68- 29
Chapter 3 Definitions	68- 7	10.5 Equipment Vent Closures.	68- 29
3.1 General.	68- 7	Chapter 11 Inspection and Maintenance	68- 30
3.2 NFPA Official Definitions.	68- 7	11.1 General.	68- 30
3.3 General Definitions.	68- 7	11.2 Design Parameters and Documentation.	68- 30
Chapter 4 General Requirements	68- 9	11.3 Installation.	68- 30
4.1 Goal.	68- 9	11.4 Inspection.	68- 30
4.2 Objectives.	68- 9	11.5 Procedures Following Vent Closure Actuation.	68- 31
4.3 Compliance Options.	68- 9	11.6 Vent Closure Design Parameters.	68- 31
Chapter 5 Performance-Based Design Option	68- 9	11.7 Inspection Reports.	68- 31
5.1 General Requirements.	68- 9	11.8 Recordkeeping.	68- 31
5.2 Performance Criteria.	68- 9	11.9 Management of Change.	68- 31
Chapter 6 Fundamentals of Venting of Deflagrations ...	68- 10	11.10 Maintenance.	68- 31
6.1 Basic Concepts.	68- 10	11.11 Employee Training.	68- 31
6.2 Mixtures.	68- 10	Annex A Explanatory Material	68- 32
6.3 Enclosure Design and Support.	68- 10	Annex B Fundamentals of Deflagration	68- 61
6.4 Enclosure Length-to-Diameter Ratio and Vent Variables.	68- 12	Annex C Guidelines for Measuring Deflagration Parameters of Dusts	68- 66
6.5 Vent Closure Operation.	68- 13	Annex D Deflagration Characteristics of Select Flammable Gases	68- 69
6.6 Consequences of a Deflagration.	68- 13	Annex E Estimating Fundamental Burning Velocity ...	68- 71
6.7 Effects of Vent Inertia.	68- 13	Annex F Deflagration Characteristics of Select Combustible Dusts	68- 72
6.8 Effects of Vent Discharge Ducts.	68- 14	Annex G Calculation Method for Correction Factor Due to Increased Vent Panel Mass	68- 74
6.9 Venting with Flame Arresting and Particulate Retention.	68- 14	Annex H Research Reports and Supporting Documents	68- 77
Chapter 7 Venting Deflagrations of Gas Mixtures and Mists	68- 15	Annex I Full and Partial Volume Gas Venting of a Building — Example Problem	68- 78
7.1 Introduction.	68- 15	Annex J Effect of Dust Partial Volumes on Venting of Buildings — Example Problem	68- 84
7.2 Venting by Means of Low Inertia Vent Closures. ..	68- 15	Annex K Bibliography	68- 85
7.3 Partial Volume Effects.	68- 17	Annex L Informational References	68- 88
7.4 Effects of Panel Inertia.	68- 18	Index	68- 90
7.5 Effects of Vent Ducts.	68- 18		
7.6 Fireball Dimensions.	68- 19		
7.7 Deflagration Venting of Enclosures Interconnected with Pipelines.	68- 19		
Chapter 8 Venting of Deflagrations of Dusts and Hybrid Mixtures	68- 19		
8.1 Introduction.	68- 19		
8.2 Venting by Means of Low-Inertia Vent Closures. ..	68- 19		
8.3 Effects of Panel Inertia.	68- 21		
8.4 Effects of Partial Volume.	68- 21		
8.5 Effects of Vent Ducts.	68- 23		
8.6 Bins, Hoppers, and Silos.	68- 24		
8.7 Venting of Dust Collectors Using Bags, Filters, or Cartridges.	68- 24		
8.8 Bucket Elevators.	68- 25		
8.9 Fireball Dimensions.	68- 25		

NFPA 68

Standard on

Explosion Protection by Deflagration Venting

2018 Edition

IMPORTANT NOTE: This NFPA document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notices and Disclaimers Concerning NFPA Standards.” They can also be viewed at www.nfpa.org/disclaimers or obtained on request from NFPA.

UPDATES, ALERTS, AND FUTURE EDITIONS: New editions of NFPA codes, standards, recommended practices, and guides (i.e., NFPA Standards) are released on scheduled revision cycles. This edition may be superseded by a later one, or it may be amended outside of its scheduled revision cycle through the issuance of Tentative Interim Amendments (TIAs). An official NFPA Standard at any point in time consists of the current edition of the document, together with all TIAs and Errata in effect. To verify that this document is the current edition or to determine if it has been amended by TIAs or Errata, please consult the National Fire Codes® Subscription Service or the “List of NFPA Codes & Standards” at www.nfpa.org/docinfo. In addition to TIAs and Errata, the document information pages also include the option to sign up for alerts for individual documents and to be involved in the development of the next edition.

NOTICE: An asterisk (*) following the number or letter designating a paragraph indicates that explanatory material on the paragraph can be found in Annex A.

A reference in brackets [] following a section or paragraph indicates material that has been extracted from another NFPA document. As an aid to the user, the complete title and edition of the source documents for extracts in mandatory sections of the document are given in Chapter 2 and those for extracts in informational sections are given in Annex L. Extracted text may be edited for consistency and style and may include the revision of internal paragraph references and other references as appropriate. Requests for interpretations or revisions of extracted text shall be sent to the technical committee responsible for the source document.

Information on referenced publications can be found in Chapter 2 and Annexes H, K, and L.

Chapter 1 Administration

1.1* Scope. This standard applies to the design, location, installation, maintenance, and use of devices and systems that vent the combustion gases and pressures resulting from a deflagration within an enclosure so that structural and mechanical damage is minimized.

1.2* Purpose. The purpose of this standard is to provide the user with criteria for design, installation, and maintenance of deflagration vents and associated components.

1.3* Application. This standard applies where the need for deflagration venting has been established.

1.3.1 This standard does not apply to detonations, bulk auto-ignition of gases, or unconfined deflagrations, such as open-air or vapor cloud explosions.

1.3.2* This standard does not apply to devices that are designed to protect storage vessels against excess internal pressure due to external fire exposure or to exposure to other heat sources.

1.3.3 This standard does not apply to emergency vents for pressure generated during runaway exothermic reactions, self-decomposition reactions, internal vapor generation resulting from electrical faults, or pressure generation mechanisms other than deflagration.

1.3.4 This standard does not apply to venting of deflagrations in oxygen-enriched atmospheres or other oxidants unless supported by specific test data.

1.4 Retroactivity.

1.4.1 The provisions of this standard reflect a consensus of what is necessary to provide an acceptable degree of protection from the hazards addressed in this standard at the time the standard was issued.

1.4.1.1 Unless otherwise specified, the provisions of this standard shall not apply to facilities, equipment, structures, or installations that existed or were approved for construction or installation prior to the effective date of the standard. Where specified, the provisions of this standard shall be retroactive.

1.4.1.2 In those cases where the authority having jurisdiction determines that the existing situation presents an unacceptable degree of risk, the authority having jurisdiction shall be permitted to apply retroactively any portions of this standard deemed appropriate.

1.4.1.3 The retroactive requirements of this standard shall be permitted to be modified if their application clearly would be impractical in the judgment of the authority having jurisdiction, and only where it is clearly evident that a reasonable degree of safety is provided.

1.4.2 This standard shall apply to facilities on which construction is begun subsequent to the date of publication of the standard.

1.4.3 When major replacement or renovation of existing facilities is planned, provisions of this standard shall apply.

1.5 Equivalency. Nothing in this standard is intended to prevent the use of systems, methods, or devices of equivalent or superior quality, strength, fire resistance, effectiveness, durability, and safety over those prescribed by this standard.

1.5.1 Technical documentation shall be submitted to the authority having jurisdiction to demonstrate equivalency.

1.5.2 The system, method, or device shall be approved for the intended purpose by the authority having jurisdiction.

▲ 1.6 Conversion Factors. The conversion factors in Table 1.6 are useful for understanding the data presented in this standard.

Table 1.6 Conversion Factors

Parameter	Unit	Equivalent
Length	1 m	3.28 ft 39.4 in.
	1 in.	25.4 mm
	1 ft	305 mm
	1 μm	1.00×10^{-6} m
Area	1 m ²	10.8 ft ²
	1 in. ²	6.45 cm ²
Volume	1 L	61.0 in. ³
	1 ft ³	7.48 U.S. gal
	1 m ³	35.3 ft ³ 264 U.S. gal
	1 U.S. gal	3.78 L 231 in. ³
		0.134 ft ³
Pressure	1 atm	760 mm Hg 101 kPa 14.7 psi 1.01 bar
	1 psi	6.89 kPa
	1 N/m ²	1.00 Pa
	1 bar	100 kPa 14.5 psi 0.987 atm
	1 kg/cm ²	14.2 psi
	1 kg/m ²	0.205 lb/ft ² (psf)
Energy	1 J	1.00 W-s
	1 Btu	1055 J
	1 J	0.738 ft-lb
K_{St}	1 bar-m/s	47.6 psi-ft/s
conversion	1 psi-ft/s	0.021 bar-m/s
Concentration	1 oz avoirdupois/ft ³	1000 g/m ³

Key to abbreviations:

atm = atmosphere

Btu = British thermal unit

cm = centimeter

ft = foot

g = gram

gal = gallon

Hg = mercury

in. = inch

J = joule

kg = kilogram

kPa = kilopascal

L = liter

lb = pound

m = meter

mm = millimeter

N = newton

oz = ounce

Pa = pascal

psf = pounds per square foot

psi = pounds per square inch

s = second

W = watt

 μm = micron (micrometer)**1.7 Symbols.** The following symbols are defined for the purpose of this standard:

A	=	area (m ² , ft ² , or in. ²)
A_s	=	internal surface area of enclosure (m ² or ft ²)
A_v	=	vent area (m ² or ft ²)
C	=	constant used in venting equations as defined in each specific use
dP/dt	=	rate of pressure rise (bar/s or psi/s)
F_r	=	reaction force constant (lb)
K_{St}	=	deflagration index for dusts (bar-m/s)
L_n	=	linear dimension of enclosure [m or ft ($n = 1, 2, 3$)]
L_x	=	distance between adjacent vents
L/D	=	length to diameter ratio (dimensionless)
LFL	=	lower flammable limit (percent by volume for gases, weight per volume for dusts and mists)
MEC	=	minimum explosible concentration (g/m ³ or oz/ft ³)
MIE	=	minimum ignition energy (mJ)
p	=	perimeter of duct cross-section (m or ft)
P	=	pressure (bar-g or psig)
P_{es}	=	enclosure strength (bar-g or psig)
P_{ex}	=	explosion pressure (bar-g or psig)
P_{max}	=	maximum pressure developed in an unvented vessel (bar-g or psig)
P_0	=	initial pressure (bar-g or psig)
P_{red}	=	reduced pressure [i.e., maximum pressure actually developed during a vented deflagration (bar-g or psig)]
P_{stat}	=	static activation pressure (bar-g or psig)
dP	=	pressure differential (bar or psi)
S_u	=	fundamental burning velocity (cm/s)
S_f	=	flame speed (cm/s)
t_f	=	duration of pressure pulse (s)
UFL	=	upper flammable limit (percent by volume)
V	=	volume (m ³ or ft ³)

1.8 Pressure. All pressures are gauge pressure unless otherwise specified.**Chapter 2 Referenced Publications****2.1 General.** The documents or portions thereof listed in this chapter are referenced within this standard and shall be considered part of the requirements of this document.**2.2 NFPA Publications.** National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169-7471.NFPA 69, *Standard on Explosion Prevention Systems*, 2014 edition.NFPA 70®, *National Electrical Code®*, 2017 edition.NFPA 654, *Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids*, 2017 edition.NFPA 704, *Standard System for the Identification of the Hazards of Materials for Emergency Response*, 2017 edition.

2.3 Other Publications.

- ▲ **2.3.1 API Publications.** American Petroleum Institute, 1220 L Street, NW, Washington, DC 20005-4070.

API STD 650, *Welded Tanks for Oil Storage*, 2013, Errata, 2014.

- 2.3.2 ASME Publications.** ASME International, Two Park Avenue, New York, NY 10016-5990.

ASME Boiler and Pressure Vessel Code, 2015.

- 2.3.3 ASTM Publications.** ASTM International, 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959.

ASTM E1226, *Standard Test Method for Explosibility of Dust Clouds*, 2012A.

- 2.3.4 ISO Publications.** International Organization for Standardization, ISO Central Secretariat, BIBC II, Chemin de Blandonnet 8, CP 401, 1214 Vernier, Geneva, Switzerland.

ISO 6184-1, *Explosion protection systems — Part 1: Determination of explosion indices of combustible dust in air*, 1985.

2.3.5 Other Publications.

Merriam-Webster's Collegiate Dictionary, 11th edition, Merriam-Webster, Inc., Springfield, MA, 2003.

2.4 References for Extracts in Mandatory Sections.

NFPA 53, *Recommended Practice on Materials, Equipment, and Systems Used in Oxygen-Enriched Atmospheres*, 2016 edition.

NFPA 652, *Standard on the Fundamentals of Combustible Dust*, 2016 edition.

NFPA 654, *Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids*, 2017 edition.

Chapter 3 Definitions

3.1 General. The definitions contained in this chapter shall apply to the terms used in this standard. Where terms are not defined in this chapter or within another chapter, they shall be defined using their ordinarily accepted meanings within the context in which they are used. *Merriam-Webster's Collegiate Dictionary*, 11th edition, shall be the source for the ordinarily accepted meaning.

3.2 NFPA Official Definitions.

3.2.1* Approved. Acceptable to the authority having jurisdiction.

3.2.2* Authority Having Jurisdiction (AHJ). An organization, office, or individual responsible for enforcing the requirements of a code or standard, or for approving equipment, materials, an installation, or a procedure.

3.2.3 Labeled. Equipment or materials to which has been attached a label, symbol, or other identifying mark of an organization that is acceptable to the authority having jurisdiction and concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials, and by whose labeling the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

3.2.4* Listed. Equipment, materials, or services included in a list published by an organization that is acceptable to the authority having jurisdiction and concerned with evaluation of products or services, that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services, and whose listing states that either the equipment, material, or service meets appropriate designated standards or has been tested and found suitable for a specified purpose.

3.2.5 Shall. Indicates a mandatory requirement.

3.2.6 Should. Indicates a recommendation or that which is advised but not required.

3.2.7 Standard. An NFPA Standard, the main text of which contains only mandatory provisions using the word “shall” to indicate requirements and that is in a form generally suitable for mandatory reference by another standard or code or for adoption into law. Nonmandatory provisions are not to be considered a part of the requirements of a standard and shall be located in an appendix, annex, footnote, informational note, or other means as permitted in the NFPA Manuals of Style. When used in a generic sense, such as in the phrase “standards development process” or “standards development activities,” the term “standards” includes all NFPA Standards, including Codes, Standards, Recommended Practices, and Guides.

3.3 General Definitions.

3.3.1 Burning Velocity. The rate of flame propagation relative to the velocity of the unburned gas that is ahead of it.

3.3.1.1 Fundamental Burning Velocity. The burning velocity of a laminar flame under stated conditions of composition, temperature, and pressure of the unburned gas.

3.3.2 Combustible Dust. A finely divided combustible particulate solid that presents a flash fire hazard or explosion hazard when suspended in air or the process-specific oxidizing medium over a range of concentrations. [654, 2017]

3.3.3 Combustion. A chemical process of oxidation that occurs at a rate fast enough to produce heat and usually light in the form of either a glow or flame.

3.3.4 Deflagration. Propagation of a combustion zone at a velocity that is less than the speed of sound in the unreacted medium.

- ▲ **3.3.5 Deflagration Index.** Value indicated by the use of the variable K . (See 3.3.20, K_{St})

3.3.6 Detonation. Propagation of a combustion zone at a velocity greater than the speed of sound in the unreacted medium.

3.3.7* Enclosure. A confined or partially confined volume.

3.3.8 Equivalent Diameter. See 3.3.19, Hydraulic Diameter.

3.3.9 Explosible. A material with a pressure ratio (maximum pressure/pressure at ignition, in absolute units) equal to or greater than 2.0 in any test when tested using the explosibility or Go/No-Go screening test described in Section 13 of ASTM E1226, *Standard Test Method for Explosibility of Dust Clouds*.