

**NFPA®**

**204**

---

**Standard for  
Smoke and Heat Venting**

---

**2018**



This is a preview. [Click here to purchase the full publication.](#)

## IMPORTANT NOTICES AND DISCLAIMERS CONCERNING NFPA® STANDARDS

### NOTICE AND DISCLAIMER OF LIABILITY CONCERNING THE USE OF NFPA STANDARDS

NFPA® codes, standards, recommended practices, and guides (“NFPA Standards”), of which the document contained herein is one, are developed through a consensus standards development process approved by the American National Standards Institute. This process brings together volunteers representing varied viewpoints and interests to achieve consensus on fire and other safety issues. While the NFPA administers the process and establishes rules to promote fairness in the development of consensus, it does not independently test, evaluate, or verify the accuracy of any information or the soundness of any judgments contained in NFPA Standards.

The NFPA disclaims liability for any personal injury, property, or other damages of any nature whatsoever, whether special, indirect, consequential or compensatory, directly or indirectly resulting from the publication, use of, or reliance on NFPA Standards. The NFPA also makes no guaranty or warranty as to the accuracy or completeness of any information published herein.

In issuing and making NFPA Standards available, the NFPA is not undertaking to render professional or other services for or on behalf of any person or entity. Nor is the NFPA undertaking to perform any duty owed by any person or entity to someone else. Anyone using this document should rely on his or her own independent judgment or, as appropriate, seek the advice of a competent professional in determining the exercise of reasonable care in any given circumstances.

The NFPA has no power, nor does it undertake, to police or enforce compliance with the contents of NFPA Standards. Nor does the NFPA list, certify, test, or inspect products, designs, or installations for compliance with this document. Any certification or other statement of compliance with the requirements of this document shall not be attributable to the NFPA and is solely the responsibility of the certifier or maker of the statement.

### REVISION SYMBOLS IDENTIFYING CHANGES FROM THE PREVIOUS EDITION

Text revisions are shaded. A **Δ** before a section number indicates that words within that section were deleted and a **Δ** to the left of a table or figure number indicates a revision to an existing table or figure. When a chapter was heavily revised, the entire chapter is marked throughout with the **Δ** symbol. Where one or more sections were deleted, a **•** is placed between the remaining sections. Chapters, annexes, sections, figures, and tables that are new are indicated with an **N**.

Note that these indicators are a guide. Rearrangement of sections may not be captured in the markup, but users can view complete revision details in the First and Second Draft Reports located in the archived revision information section of each code at [www.nfpa.org/docinfo](http://www.nfpa.org/docinfo). Any subsequent changes from the NFPA Technical Meeting, Tentative Interim Amendments, and Errata are also located there.

### REMINDER: UPDATING OF NFPA STANDARDS

Users of NFPA codes, standards, recommended practices, and guides (“NFPA Standards”) should be aware that NFPA Standards may be amended from time to time through the issuance of a Tentative Interim Amendment (TIA) or corrected by Errata. An official NFPA Standard at any point in time consists of the current edition of the document together with any TIAs and Errata then in effect.

To determine whether an NFPA Standard has been amended through the issuance of Tentative Interim Amendments or corrected by Errata, go to [www.nfpa.org/docinfo](http://www.nfpa.org/docinfo) to choose from the list of NFPA Standards or use the search feature to select the NFPA Standard number (e.g., NFPA 13). The document information page provides up-to-date document-specific information as well as postings of all existing TIAs and Errata. It also includes the option to register for an “Alert” feature to receive an automatic email notification when new updates and other information are posted regarding the document.

# IMPORTANT NOTICES AND DISCLAIMERS CONCERNING NFPA® STANDARDS

## ADDITIONAL NOTICES AND DISCLAIMERS

### Updating of NFPA Standards

Users of NFPA codes, standards, recommended practices, and guides (“NFPA Standards”) should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of Tentative Interim Amendments or corrected by Errata. An official NFPA Standard at any point in time consists of the current edition of the document together with any Tentative Interim Amendments and any Errata then in effect. In order to determine whether a given document is the current edition and whether it has been amended through the issuance of Tentative Interim Amendments or corrected through the issuance of Errata, consult appropriate NFPA publications such as the National Fire Codes® Subscription Service, visit the NFPA website at [www.nfpa.org](http://www.nfpa.org), or contact the NFPA at the address listed below.

### Interpretations of NFPA Standards

A statement, written or oral, that is not processed in accordance with Section 6 of the Regulations Governing the Development of NFPA Standards shall not be considered the official position of NFPA or any of its Committees and shall not be considered to be, nor be relied upon as, a Formal Interpretation.

### Patents

The NFPA does not take any position with respect to the validity of any patent rights referenced in, related to, or asserted in connection with an NFPA Standard. The users of NFPA Standards bear the sole responsibility for determining the validity of any such patent rights, as well as the risk of infringement of such rights, and the NFPA disclaims liability for the infringement of any patent resulting from the use of or reliance on NFPA Standards.

NFPA adheres to the policy of the American National Standards Institute (ANSI) regarding the inclusion of patents in American National Standards (“the ANSI Patent Policy”), and hereby gives the following notice pursuant to that policy:

NOTICE: The user’s attention is called to the possibility that compliance with an NFPA Standard may require use of an invention covered by patent rights. NFPA takes no position as to the validity of any such patent rights or as to whether such patent rights constitute or include essential patent claims under the ANSI Patent Policy. If, in connection with the ANSI Patent Policy, a patent holder has filed a statement of willingness to grant licenses under these rights on reasonable and nondiscriminatory terms and conditions to applicants desiring to obtain such a license, copies of such filed statements can be obtained, on request, from NFPA. For further information, contact the NFPA at the address listed below.

### Law and Regulations

Users of NFPA Standards should consult applicable federal, state, and local laws and regulations. NFPA does not, by the publication of its codes, standards, recommended practices, and guides, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

### Copyrights

NFPA Standards are copyrighted. They are made available for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of safe practices and methods. By making these documents available for use and adoption by public authorities and private users, the NFPA does not waive any rights in copyright to these documents.

Use of NFPA Standards for regulatory purposes should be accomplished through adoption by reference. The term “adoption by reference” means the citing of title, edition, and publishing information only. Any deletions, additions, and changes desired by the adopting authority should be noted separately in the adopting instrument. In order to assist NFPA in following the uses made of its documents, adopting authorities are requested to notify the NFPA (Attention: Secretary, Standards Council) in writing of such use. For technical assistance and questions concerning adoption of NFPA Standards, contact NFPA at the address below.

### For Further Information

All questions or other communications relating to NFPA Standards and all requests for information on NFPA procedures governing its codes and standards development process, including information on the procedures for requesting Formal Interpretations, for proposing Tentative Interim Amendments, and for proposing revisions to NFPA standards during regular revision cycles, should be sent to NFPA headquarters, addressed to the attention of the Secretary, Standards Council, NFPA, 1 Batterymarch Park, P.O. Box 9101, Quincy, MA 02269-9101; email: [stds\\_admin@nfpa.org](mailto:stds_admin@nfpa.org).

For more information about NFPA, visit the NFPA website at [www.nfpa.org](http://www.nfpa.org). All NFPA codes and standards can be viewed at no cost at [www.nfpa.org/docinfo](http://www.nfpa.org/docinfo).

Copyright © 2017, National Fire Protection Association®. All Rights Reserved.

## NFPA® 204

### Standard for

## Smoke and Heat Venting

### 2018 Edition

This edition of NFPA 204, *Standard for Smoke and Heat Venting*, was prepared by the Technical Committee on Smoke Management Systems. It was issued by the Standards Council on November 10, 2017, with an effective date of November 30, 2017, and supersedes all previous editions.

This edition of NFPA 204 was approved as an American National Standard on November 30, 2017.

### Origin and Development of NFPA 204

This project was initiated in 1956 when the NFPA Board of Directors referred the subject to the Committee on Building Construction. A tentative guide was submitted to NFPA in 1958. Revised and tentatively adopted in 1959 and again in 1960, the guide was officially adopted in 1961. In 1968, a revised edition was adopted that included a new section, Inspection and Maintenance.

In 1975, a reconfirmation action failed as concerns over use of the guide in conjunction with automatic sprinklered buildings surfaced. Because of this controversy, work on a revision to the guide continued at a slow pace.

The Technical Committee and Subcommittee members agreed that the state of the art had progressed sufficiently to develop improved technology-based criteria for design of venting; therefore, the 1982 edition of the document represented a major advance in engineered smoke and heating venting, although reservations over vent and sprinkler applications still existed.

At the time the guide was formulated, the current venting theory was considered unwieldy for this format; consequently, the more adaptable theory as described herein was adopted.

Appreciation must be extended to Dr. Gunnar Heskestad at the Factory Mutual Research Corporation (now FM Global) for his major contribution to the theory applied in this standard, which is detailed in Annex B.

The 1985 edition again revised Chapter 6 on the subject of venting in sprinklered buildings. Test data from work done at the Illinois Institute of Technology Research, which had been submitted to the Committee as part of a public proposal, did not permit consensus to be developed on whether sprinkler control was impaired or enhanced by the presence of automatic roof vents of typical spacing and area. The revised wording of Chapter 6 encouraged the designer to use the available tools and data referenced in the document while the use of automatic venting in sprinklered buildings was under review.

The 1991 edition made minor changes to Chapter 6 to acknowledge that a design basis existed for using sprinklers and automatic heat venting together but that such had not received wide recognition.

The 1998 edition represented a complete revision of the guide. The rewrite deleted the previous tables that listed vent areas and incorporated engineering equations and referenced computer models, such as LAVENT and DETACT, to provide the designer with the necessary tools to develop vent designs based on performance objectives. This rewrite was based extensively on state-of-the-art technology published in the references. In many cases, the authors of these references participated in the task group's rewrite efforts.

The 2002 edition of NFPA 204 was converted from a guide to a standard, thus implementing mandatory requirements and updated language. The document was also updated to meet *Manual of Style for NFPA Technical Committee Documents* requirements.

The 2007 edition included a number of technical changes. New provisions on air entrainment into the fire plume, the effect of wind on the location of air vents, sizing of air paths, air velocity limitations, and plugholing were provided.

Information on the use of vents as air inlets and a better description of the smoke layer interface were added. Revisions with regard to how heat release rates, discharge coefficients, exhaust rates, and the number of exhaust inlets are to be determined were incorporated. Reference to international standards on vents, mechanical smoke extract, and draft curtains, as well as updated annex text on recent research efforts, were provided.

The 2012 edition was updated to include additional requirements and annex material for venting in sprinklered buildings.

The 2015 edition included revised provisions on draft curtains. These requirements created consistency with NFPA 92.

The 2018 edition was updated to include a correction to an Annex A image, the addition of a definition for the term “standard,” and updated references.

## Technical Committee on Smoke Management Systems

**Allyn J. Vaughn**, *Chair*

NV5/JBA Consulting Engineers, NV [SE]

**Elyahu Avidor**, Tel Aviv, Israel [RT]

Rep. Standards Institution of Israel

**Carl F. Baldassarra**, Wiss Janney Elstner Associates, Inc., IL [SE]

**Flora F. Chen**, Hayward Fire Department, California, CA [E]

**Richard J. Davis**, FM Global, MA [I]

**Kevin L. Derr**, U.S. Architect of the Capitol, DC [E]

**Kelly Eisenstein**, City Of San Diego, CA [E]

**Michael J. Ferreira**, JENSEN HUGHES, MD [SE]

**Donald Fess**, Harvard University, MA [U]

**Maxwell French**, Cosentini Associates, MA [SE]

**Brian Green**, Viking Corporation, MI [M]

Rep. National Fire Sprinkler Association

**Geoffrey Harris**, Smoke and Fire Engineering Technology Ltd., United Kingdom [SE]

Rep. ISO TC on Smoke and Heat Control Systems and Components

**David A. Killian**, Walt Disney Parks & Resorts, CA [U]

**William E. Koffel**, Koffel Associates, Inc., MD [M]

Rep. AAMA Smoke Vent Task Group

**Jeffrey A. Maddox**, The Fire Consultants, Inc., CA [SE]

**Cameron J. McCartney**, National Research Council of Canada, Canada [RT]

**James A. Milke**, University of Maryland, MD [SE]

**Timothy J. Orris**, AMCA International, Inc., IL [M]

Rep. Air Movement & Control Association

**Thomas J. Parrish**, Telgian Corporation, MI [M]

Rep. Automatic Fire Alarm Association, Inc.

**Joseph Plati**, Code Consultants, Inc., NY [SE]

**James R. Richardson**, Lisle Woodridge Fire District, IL [E]

**Lawrence J. Shudak**, UL LLC, IL [RT]

**Deo Suriya Supanavongs**, Honeywell International Inc., IL [M]

Rep. National Electrical Manufacturers Association

**Jeffrey S. Tubbs**, Arup, MA [SE]

**Paul G. Turnbull**, Siemens Building Technologies, Inc., IL [M]

**Michael J. Ventola**, Space Age Electronics, FL [M]

**Stacy N. Welch**, Marriott International, Inc., MD [U]

**Peter J. Willse**, Global Asset Protection Services, LLC, CT [I]

### Alternates

**Sanjay Aggarwal**, JENSEN HUGHES, CA [SE]

(Alt. to Michael J. Ferreira)

**Mark Allen Belke**, Greenheck Fan Corporation, WI [M]

(Alt. to Timothy J. Orris)

**Diane B. Copeland**, Dillon Consulting Engineers, Inc., CA [SE]

(Voting Alternate)

**Jason Daniels**, Code Consultants, Inc., MO [SE]

(Alt. to Joseph Plati)

**Donald G. Goosman**, Wiss Janney Elstner Associates, Inc., IL [SE]

(Alt. to Carl F. Baldassarra)

**Gary D. Loughheed**, National Research Council of Canada, Canada [RT]

(Alt. to Cameron J. McCartney)

**Zachary L. Magnone**, Tyco Fire Protection Products, RI [M]

(Alt. to Brian Green)

**Wesley Marcks**, Xtralis, Inc., MA [M]

(Alt. to Deo Suriya Supanavongs)

**Andrew Neviackas**, Arup, MA [SE]

(Alt. to Jeffrey S. Tubbs)

**Gregory K. Shino**, NV5/JBA Consulting Engineers, NV [SE]

(Alt. to Allyn J. Vaughn)

**Luke C. Woods**, UL LLC, MA [RT]

(Alt. to Lawrence J. Shudak)

**Brittany Dawn Wright**, Walt Disney Parks & Resorts, FL [U]

(Alt. to David A. Killian)

**Yibing Xin**, FM Global, MA [I]

(Alt. to Richard J. Davis)

### Nonvoting

**Christian Norgaard Madsen**, Norconsult, Norway [SE]

**Bent A. Borresen**, Norconsult, Norway [SE]

(Alt. to Christian Norgaard Madsen)

**Brian J. O'Connor**, NFPA Staff Liaison

**John H. Klote**, Leesburg, VA [SE]

(Member Emeritus)

*This list represents the membership at the time the Committee was balloted on the final text of this edition. Since that time, changes in the membership may have occurred. A key to classifications is found at the back of the document.*

NOTE: Membership on a committee shall not in and of itself constitute an endorsement of the Association or any document developed by the committee on which the member serves.

**Committee Scope:** This Committee shall have primary responsibility for documents on the design, installation, testing, operation, and maintenance of systems for the control, removal, or venting of heat or smoke from fires in buildings.

## Contents

<b>Chapter 1 Administration</b> .....	204- 5	8.3 Growing (Continuous-Growth) Fires. ....	204- 12
1.1 Scope. ....	204- 5	<b>Chapter 9 Sizing Vents</b> .....	204- 12
1.2 Purpose. (Reserved) .....	204- 5	9.1 General. ....	204- 12
1.3 Application. ....	204- 5	9.2 Hand Calculations. ....	204- 13
1.4 Retroactivity. ....	204- 5	9.3 Models. ....	204- 14
1.5 Equivalency. ....	204- 5	<b>Chapter 10 Mechanical Smoke Exhaust Systems</b> .....	204- 15
1.6 Units and Formulas. ....	204- 6	10.1 General. ....	204- 15
<b>Chapter 2 Referenced Publications</b> .....	204- 7	10.2 Exhaust Rates. ....	204- 15
2.1 General. ....	204- 7	10.3 Fire Exposure. ....	204- 15
2.2 NFPA Publications. ....	204- 7	10.4 Number of Exhaust Inlets. ....	204- 15
2.3 Other Publications. ....	204- 7	10.5 Intake Air. ....	204- 15
2.4 References for Extracts in Mandatory Sections. ....	204- 7	<b>Chapter 11 Venting in Sprinklered Buildings</b> .....	204- 15
<b>Chapter 3 Definitions</b> .....	204- 7	11.1 Design. ....	204- 15
3.1 General. ....	204- 7	11.2 Automatic Sprinkler Systems. ....	204- 15
3.2 NFPA Official Definitions. ....	204- 7	11.3 Storage Occupancies Protected by Control Mode Sprinklers. ....	204- 15
3.3 General Definitions. ....	204- 7	<b>Chapter 12 Inspection and Maintenance</b> .....	204- 16
<b>Chapter 4 Fundamentals</b> .....	204- 8	12.1 General. ....	204- 16
4.1 Design Objectives. ....	204- 8	12.2 Requirements. ....	204- 16
4.2 Design Basis. ....	204- 8	12.3 Inspection, Maintenance, and Acceptance Testing. ....	204- 16
4.3 Determination of Contents Hazard. ....	204- 8	12.4 Conduct and Observation of Operational Tests. ....	204- 16
4.4 Venting. ....	204- 8	12.5 Air Inlets. ....	204- 17
4.5 Smoke Production. ....	204- 8	12.6 Ice and Snow Removal. ....	204- 17
4.6 Vent Flows. ....	204- 9	<b>Chapter 13 Design Documentation</b> .....	204- 17
<b>Chapter 5 Vents</b> .....	204- 9	13.1 Documentation Required. ....	204- 17
5.1 Listed Vents. ....	204- 9	<b>Annex A Explanatory Material</b> .....	204- 18
5.2 Vent Design Constraints. ....	204- 9	<b>Annex B The Theoretical Basis of LAVENT</b> .....	204- 27
5.3 Methods of Operation. ....	204- 9	<b>Annex C User Guide for the LAVENT Computer Code</b> .....	204- 40
5.4 Dimensions and Spacing of Vents. ....	204- 9	<b>Annex D Sample Problem Using Engineering Equations (Hand Calculations) and LAVENT</b> .....	204- 54
5.5 Mechanical Smoke Exhaust Systems. ....	204- 9	<b>Annex E Predicting the Rate of Heat Release of Fires</b> .....	204- 69
<b>Chapter 6 Air Inlets</b> .....	204- 10	<b>Annex F Design Information</b> .....	204- 76
6.1 General. ....	204- 10	<b>Annex G Informational References</b> .....	204- 84
6.2 Construction. ....	204- 10	<b>Index</b> .....	204- 87
6.3 Location. ....	204- 10		
6.4 Installation. ....	204- 10		
6.5 Methods of Operation. ....	204- 11		
6.6 Dimensions and Spacing of Air Inlets. ....	204- 11		
6.7 Air Paths. ....	204- 11		
<b>Chapter 7 Draft Curtains</b> .....	204- 11		
7.1 General. ....	204- 11		
7.2 Construction. ....	204- 11		
7.3 Location and Depth. ....	204- 11		
7.4 Spacing. ....	204- 11		
<b>Chapter 8 The Design Fire</b> .....	204- 11		
8.1 General. ....	204- 11		
8.2 Steady (Limited-Growth) Fires. ....	204- 11		



## NFPA 204

## Standard for

## Smoke and Heat Venting

2018 Edition

**IMPORTANT NOTE:** This NFPA document is made available for use subject to important notices and legal disclaimers. These notices and disclaimers appear in all publications containing this document and may be found under the heading “Important Notices and Disclaimers Concerning NFPA Standards.” They can also be viewed at [www.nfpa.org/disclaimers](http://www.nfpa.org/disclaimers) or obtained on request from NFPA.

**UPDATES, ALERTS, AND FUTURE EDITIONS:** New editions of NFPA codes, standards, recommended practices, and guides (i.e., NFPA Standards) are released on scheduled revision cycles. This edition may be superseded by a later one, or it may be amended outside of its scheduled revision cycle through the issuance of Tentative Interim Amendments (TIAs). An official NFPA Standard at any point in time consists of the current edition of the document, together with all TIAs and Errata in effect. To verify that this document is the current edition or to determine if it has been amended by TIAs or Errata, please consult the National Fire Codes® Subscription Service or the “List of NFPA Codes & Standards” at [www.nfpa.org/docinfo](http://www.nfpa.org/docinfo). In addition to TIAs and Errata, the document information pages also include the option to sign up for alerts for individual documents and to be involved in the development of the next edition.

**NOTICE:** An asterisk (\*) following the number or letter designating a paragraph indicates that explanatory material on the paragraph can be found in Annex A.

A reference in brackets [ ] following a section or paragraph indicates material that has been extracted from another NFPA document. As an aid to the user, the complete title and edition of the source documents for extracts in mandatory sections of the document are given in Chapter 2 and those for extracts in informational sections are given in Annex G. Extracted text may be edited for consistency and style and may include the revision of internal paragraph references and other references as appropriate. Requests for interpretations or revisions of extracted text shall be sent to the technical committee responsible for the source document.

Information on referenced publications can be found in Chapter 2 and Annex G.

## Chapter 1 Administration

## 1.1 Scope.

**1.1.1\*** This standard shall apply to the design of venting systems for the emergency venting of products of combustion from fires in buildings. The provisions of Chapters 4 through 10 shall apply to the design of venting systems for the emergency venting of products of combustion from fires in nonsprinklered, single-story buildings using both hand calculations and computer-based solution methods as provided in Chapter 9. Chapter 11 shall apply to venting in sprinklered buildings.

**1.1.2\*** This standard shall not specify under which conditions venting is to be provided or required.

**1.1.3** Where a conflict exists between a general requirement and a specific requirement, the specific requirement shall be applicable.

## 1.2 Purpose. (Reserved)

## 1.3 Application.

**1.3.1\*** This standard shall not apply to ventilation within a building designed for regulation of environmental air for personnel comfort, to regulation of commercial cooking operations, to regulation of odor or humidity in toilet and bathing facilities, to regulation of cooling of production equipment, or to venting for explosion pressure relief.

**1.3.2** This standard shall apply to building construction of all types.

**1.3.3** This standard shall apply to venting fires in building spaces with ceiling heights that permit the design fire plume and smoke layer to develop.

**1.3.4\*** This standard shall apply to situations in which the hot smoke layer does not enhance the burning rate of the fuel array. Vent designs developed with this standard shall not be valid for those time intervals where smoke layer temperatures exceed 600°C (1112°F).

**1.3.5\*** This standard shall not be valid for fires having heat release rates greater than  $Q_{feasible}$  as determined in accordance with the following equation:

[1.3.5]

$$Q_{feasible} = 12,000(z_s)^{5/2}$$

where:

$Q_{feasible}$  = feasible fire heat release rate (kW)

$z_s$  = height of the smoke layer boundary above the fire base (m)

**1.3.6\*** The engineering equations or computer-based models incorporated into this standard shall be used to calculate the time duration that the smoke layer boundary is maintained at or above the design elevation in a curtained area, relative to the design interval time.

## 1.4 Retroactivity.

**1.4.1** The provisions of this standard shall not be required to be applied retroactively.

**1.4.2** Where a system is being altered, extended, or renovated, the requirements of this standard shall apply only to the work being undertaken.

**1.5 Equivalency.** Nothing in this standard is intended to prevent the use of systems, methods, or devices of equivalent or superior quality, strength, fire resistance, effectiveness, durability, and safety over those prescribed by this standard. Technical documentation shall be submitted to the authority having jurisdiction to demonstrate equivalency. The system, method, or device shall be approved for the intended purpose by the authority having jurisdiction.



**1.6 Units and Formulas.** The following symbols define the variables in the equations used throughout the body of this standard:

$A$  = area (of burning surface)  
 $A_i$  = inlet area for fresh air, below design level of smoke layer boundary  
 $A_v$  = total vent area of all vents in a curtained area  
 $\alpha$  = thermal diffusivity,  $k/\rho c$   
 $\alpha_g$  = fire growth coefficient  
 $\gamma$  = exhaust location factor (dimensionless)  
 $c_p$  = specific heat  
 $C_{d,v}$  = vent discharge coefficient  
 $C_{d,i}$  = inlet discharge coefficient  
 $d$  = smoke layer depth  
 $d_c$  = depth of draft curtain  
 $D$  = base diameter of the fire  
 $g$  = acceleration of gravity  
 $H$  = ceiling height above base of fire  
 $h_c$  = heat of combustion  
 $h_g$  = heat of gasification  
 $K$  = fraction of adiabatic temperature rise  
 $k$  = thermal conductivity  
 $k\beta$  = constant used in Equation E.5.1  
 $k\rho c$  = thermal inertia  
 $l$  = thickness  
 $L$  = mean flame height above the base of the fire  
 $L_f$  = flame length, measured from leading edge of burning region  
 $L_v$  = length of vent opening in the longer direction  
 $\dot{m}$  = mass burning rate  
 $\dot{m}''$  = mass burning rate per unit area  
 $\dot{m}_{\infty}''$  = mass burning rate per unit area for an infinite diameter pool  
 $\dot{m}_v$  = mass flow rate through vent  
 $\dot{m}_p$  = mass flow rate in the plume  
 $\dot{m}_{pl}$  = mass flow rate in the plume at mean flame height ( $L$ )  
 $\dot{q}_i''$  = incident heat flux per unit area  
 $Q$  = total heat release rate  
 $Q''$  = total heat release rate per unit floor area

$Q_c$  = convective heat release rate =  $\chi_c Q$   
 $Q_{feasible}$  = feasible fire heat release rate (kW)  
 $r$  = radius from fire axis  
 $RTI$  = response time index  $\tau u^{1/2}$   
 $\tau$  = time constant of heat-responsive element for convective heating  
 $\rho$  = density  
 $\rho_o$  = ambient air density  
 $S$  = center to center spacing of vents  
 $t$  = time  
 $t_d$  = time to detector activation  
 $t_g$  = growth time of fire  
 $t_{ig}$  = time to ignition  
 $t_r$  = design interval time  
 $t_{sa}$  = time to sprinkler activation  
 $t_{vo}$  = time to vent opening  
 $\Delta T$  = gas temperature rise (from ambient) at detector site  
 $\Delta T_a$  = adiabatic temperature rise  
 $\Delta T_e$  = temperature rise (from ambient) of heat-responsive element  
 $T$  = smoke layer temperature (K)  
 $T_o$  = ambient air temperature  
 $T_{ig}$  = ignition temperature  
 $T_s$  = surface temperature  
 $u$  = gas velocity at detector site  
 $W_{min}$  = lateral fire spread by radiation  
 $W_s$  = largest horizontal dimension of fire  
 $W_v$  = width of vent opening in the shorter direction  
 $V$  = flame spread velocity  
 $\chi_c$  = convective fraction of total heat release rate (fraction carried as heat in plume above flames) where  $\chi_c$  is a convective-heat fraction between 0.6 and 0.7  
 $\chi_r$  = radiant fraction of total heat release rate  
 $y$  = elevation of smoke layer boundary  
 $y_{ceil}$  = elevation of ceiling  
 $y_{curt}$  = elevation of bottom of draft curtain  
 $y_{fire}$  = elevation of the base of the fire above the floor  
 $z_s$  = height of the smoke layer boundary above base of fire  
 $z_{si}$  = height of the smoke layer interface above the base of the fire  
 $z_o$  = height of virtual origin above base of fire (below base of fire, if negative)

## Chapter 2 Referenced Publications

**2.1\* General.** The documents or portions thereof listed in this chapter are referenced within this standard and shall be considered part of the requirements of this document.

**2.2 NFPA Publications.** National Fire Protection Association, 1 Batterymarch Park, Quincy, MA 02169-7471.

NFPA 13, *Standard for the Installation of Sprinkler Systems*, 2016 edition.

NFPA 72®, *National Fire Alarm and Signaling Code*, 2016 edition.

### 2.3 Other Publications.

**2.3.1 FM Publications.** FM Global Technologies LLC, 270 Central Avenue, P.O. Box 7500, Johnston, RI 02919-4923.

FM 4430, *Approval Standard for Heat and Smoke Vents*, 2012.

**2.3.2 NIST Publications.** National Institute of Standards and Technology, 100 Bureau Drive, Gaithersburg, MD 20899-1070.

DETECT-QS (DETECTOR ACTuation — Quasi Steady) software.

DETECT-T2 (DETECTOR ACTuation — Time Squared) software.

LAVENT (Link-Actuated VENTS) software.

**2.3.3 UL Publications.** Underwriters Laboratories Inc., 333 Pfingsten Road, Northbrook, IL 60062-2096.

ANSI/UL 793, *Standard for Automatically Operated Roof Vents for Smoke and Heat*, 2008, revised 2016.

### 2.3.4 Other Publications.

*Merriam-Webster's Collegiate Dictionary*, 11th edition, Merriam-Webster, Inc., Springfield, MA, 2003.

## 2.4 References for Extracts in Mandatory Sections.

NFPA 72®, *National Fire Alarm and Signaling Code*, 2016 edition.

NFPA 92, *Standard for Smoke Control Systems*, 2018 edition.

NFPA 318, *Standard for the Protection of Semiconductor Fabrication Facilities*, 2018 edition.

## Chapter 3 Definitions

**3.1 General.** The definitions contained in this chapter shall apply to the terms used in this standard. Where terms are not defined in this chapter or within another chapter, they shall be defined using their ordinarily accepted meanings within the context in which they are used. *Merriam-Webster's Collegiate Dictionary*, 11th edition, shall be the source for the ordinarily accepted meaning.

### 3.2 NFPA Official Definitions.

**3.2.1\* Approved.** Acceptable to the authority having jurisdiction.

**3.2.2\* Authority Having Jurisdiction (AHJ).** An organization, office, or individual responsible for enforcing the requirements of a code or standard, or for approving equipment, materials, an installation, or a procedure.

**3.2.3 Labeled.** Equipment or materials to which has been attached a label, symbol, or other identifying mark of an organization that is acceptable to the authority having jurisdiction and concerned with product evaluation, that maintains periodic inspection of production of labeled equipment or materials, and by whose labeling the manufacturer indicates compliance with appropriate standards or performance in a specified manner.

**3.2.4\* Listed.** Equipment, materials, or services included in a list published by an organization that is acceptable to the authority having jurisdiction and concerned with evaluation of products or services, that maintains periodic inspection of production of listed equipment or materials or periodic evaluation of services, and whose listing states that either the equipment, material, or service meets appropriate designated standards or has been tested and found suitable for a specified purpose.

**3.2.5 Shall.** Indicates a mandatory requirement.

**3.2.6 Should.** Indicates a recommendation or that which is advised but not required.

**3.2.7 Standard.** An NFPA Standard, the main text of which contains only mandatory provisions using the word “shall” to indicate requirements and that is in a form generally suitable for mandatory reference by another standard or code or for adoption into law. Nonmandatory provisions are not to be considered a part of the requirements of a standard and shall be located in an appendix, annex, footnote, informational note, or other means as permitted in the NFPA Manuals of Style. When used in a generic sense, such as in the phrase “standards development process” or “standards development activities,” the term “standards” includes all NFPA Standards, including Codes, Standards, Recommended Practices, and Guides.

## 3.3 General Definitions.

**3.3.1 Ceiling Jet.** A flow of smoke under the ceiling, extending radially from the point of fire plume impingement on the ceiling.

**3.3.2 Clear (Air) Layer.** The zone within a building containing air that has not been contaminated by the smoke produced from a fire in the building, and that is located between the floor and the smoke layer boundary.

**3.3.3\* Clear Layer Interface.** The boundary between a smoke layer and smoke-free air.

**3.3.4 Continuously Growing Fires.** Fires that, if unchecked, will continue to grow over the design interval time.

**3.3.5 Curtained Area.** An area of a building that has its perimeter delineated by draft curtains, full height partitions, exterior walls, or any combinations thereof.

**3.3.6 Design Depth of the Smoke Layer.** The difference between the height of the ceiling and the minimum height of the smoke layer boundary above the finished floor level that meets design objectives.

**3.3.7 Design Fire.** As used in this standard, the time-rate heat release history selected as the input for the calculations prescribed herein.