

AEROSPACE RECOMMENDED PRACTICE

ARP5526™

REV. E

Issued Revised 2003-01 2018-08

Superseding ARP5526D

(R) Aircraft Seat Design Guidance and Clarifications

RATIONALE

The change in this revision represents the latest agreement obtained by the SAE SEAT Committee to include the latest industry needs in regard to lifevest stowage ease of search and evaluation of surfaces within the head strike zone.

TABLE OF CONTENTS

1.	SCOPE	5
2.	APPLICABLE DOCUMENTS	5
2.1	SAE Publications	
2.2	NAS Publications	
2.3	CFR Publications	5
2.4	FAA Publications	
2.5	Civil Aerospace Medical Institute	
2.6	NASA Publications	6
2.7	UL Publications	
2.8	RTCA Publications	
0	DECOMMENDED DRACTICES	
3. 3.1	RECOMMENDED PRACTICESSeat Back Handhold in Turbulence	
3.1.1		
3.1.1	Applicable Policy and Regulations	
_	Recommended Practice	
3.2	Seat Belt Misalignment/Disengagement	
3.2.1 3.2.2	Applicable Policy and Regulations	
3.2.2	Recommended Practice	
	Examples	
3.2.4	Y-Belts	
3.3 3.3.1	Life Vest/Life Jacket Retrieval	
	Applicable Policy and Regulations	
3.3.2	Recommended Practice	
3.3.3	Life Vests in Leg Rests Considerations	
3.4	Friction Fit Components	
3.4.1	Applicable Policy and Regulations	
3.4.2	Recommended Practice	
3.5	Fire Containment - Cavity Fully Enclosed/Open	
3.5.1	Applicable Policy and Regulations	
3.5.2	Recommended Practice	
3.6	Hinged Aisle Armrests - Discreet Latch	
3.6.1	Applicable Policy and Regulations	
3.6.2	Recommended Practice	16

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2018 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER:

Tel: 877-606-7323 (inside USA and Canada)

SAE values your input. To provide feedback

526E

This is a preview. Click here to purchase the full publication.

3.7	Baggage Bar Loading and Retention of Items under the Seat	
3.7.1	Applicable Policy and Regulations	
3.7.2	Recommended Practice	
3.8	Seat Safety Placards	20
3.8.1	Applicable Policy and Regulations	20
3.8.2	Recommended Practice	
3.9	Literature Pocket Stowage Capacity	20
3.9.1	Applicable Policy and Regulations	20
3.9.2	Recommended Practice	
3.10	Seat Back Mounted Tray Table Latch Inadvertent Operation	22
3.10.1	Applicable Policy and Regulations	
3.10.2	Recommended Practice	
3.11	Pinch Hazards	24
3.11.1	Applicable Policy and Regulations	24
3.11.2	Recommended Practice	
3.12	Sharp Edges	29
3.12.1	Applicable Policy and Regulations	
3.12.2	Recommended Practice	
3.13	Evaluation of Surfaces within Head Strike Zone	
3.13.1	Applicable Policy and Regulations	
3.13.2	Recommended Practice	
3.14	Seat Features Adjusted with/without Tools	
3.14.1	Applicable Policy and Regulations	
3.14.2	Recommended Practice	34
3.15	Leg Rest and Footbar Retention	
3.15.1	Applicable Policy and Regulations	35
3.15.2	Recommended Practice	36
3.16	Emergency Escape Path Marking	36
3.16.1	Applicable Policy and Regulations	36
3.16.2	Recommended Practice	36
3.17	Rotating and Translating Armrests	
3.17.1	Applicable Policy and Regulations	
3.17.2	Recommended Practice	
3.18	Electrically Actuated Features	
3.18.1	Applicable Policy and Regulations	
3.18.2	Recommended Practice	
3.18.3	Further Information	
3.19	Crew Size	
3.19.1	Applicable Policy and Regulations	
3.20	Occupant height	
3.20.1	Recommended Practice	
3.21	Occupant Size	
3.21.1	Applicable Policy and Regulations	
3.21.2	Recommended Practice	
3.22	Attendant Step	
3.22.1	Applicable Policy and Regulations	
3.22.2	Recommended Practice	
3.23	Wear and Deterioration	
3.23.1	Applicable Policy and Regulations	
3.23.2 3.24	Recommended Practice	
	Fire Protection Requirements	
3.24.1 3.24.2	Applicable Policy and Regulations	
3.24.2 3.25	Anti-Rattle Device	
3.25 3.25.1	Applicable Policy and Regulations	
3.25.1 3.25.2	Recommended Practice	
3.25.2 3.26	Recline Egress	
3.26.1	Applicable Policy and Regulations	
3.26.2	Recommended Practice	
2.20.2	Abuse Leads for Cocondary Structures	

3.27.1	Applicable Policy and Regulations	53
3.27.2	Recommended Practice	
3.28	Fatigue Life Criteria	54
3.28.1	Applicable Policy and Regulations	
3.28.2	Recommended Practice	
3.29	Leg Rest and Footrest Definition	
3.29.1	Applicable Policy and Regulations	
3.29.2	Recommended Practice	
3.30	SRP	56
3.30.1	Applicable Policy and Regulations	56
3.30.2	Recommended Practice	56
3.31	Life Vest Stowage Ease of Search	58
3.31.1	Application Policy and Regulations	58
3.31.2	Recommended Practice	
3.32	Manual Override for TTL Position of Electrically Operated Seats	
3.32.1	Applicable Policy and Regulations	
3.32.2	Recommended Practice	
3.33	Environmentally Preferable Material	
3.33.1	Applicable Policy and Regulations	
3.33.2	Recommended Practice	61
4.	NOTES	61
4.1	Revision Indicator	
Figure 1	Seat belt misalignment	c
Figure 2	Seat belt misalignment	
Figure 3	An example of a design to avoid	
Figure 4	An example of a design to avoid	
Figure 5	An example of a design to avoid	
Figure 6	An example of a design to avoid	
Figure 7	Seat Y-belt misalignment	
Figure 8	Belt cover non-permanent attachment	
Figure 9	Economy seat - planes defining the boundaries of underseat stowage	
Figure 10	All other seats - planes defining the boundaries of underseat stowage	
Figure 11A	Acceptable angle for upper surface of underseat stowage volume	19
Figure 11B	Acceptable complex shape for upper surface of underseat stowage volume	19
Figure 12	Literature pocket size recommendations	21
Figure 13	External pockets	22
Figure 14	This is the hinge for an in-arm video display. It is an example of a type 1A score from the injury potential analysis table	25
Figure 15	This is the arm cap for an in-arm tray table seat. It is an example of a type 1A score from the injury	20
•	potential analysis table	26
Figure 16	This is a hinge for an in-arm tray table. It is an example of a type 1A score from the injury	
Figure 17	potential analysis table	26
Figure 17	This is a spring mounted stowage box door. It is an example of a type 4A score from the injury potential analysis table based on spring force potential	27
Figure 18	This is an aft mounted food tray table. It is an example of a type 1A score from the injury potential	∠1
	analysis table.	27
Figure 19	This is the hinge point for a rotating armrest. It is an example of a type 2B score from the injury	
	potential analysis table	28
Figure 20A	Seat back sharp edges head strike zone width (HIC compliant)	
Figure 20B	Seat back sharp edges head strike zone upper and lower height (HIC compliant)	
Figure 21	Head strike zone definition (non- HIC compliant)	
Figure 22	Hazard determination chart	
Figure 23	Leg rest measurement points for moving parts	
Figure 24	Armrest measurement points for moving parts	42
Figure 25	Seat back measurement points for moving parts	
Figure 26	Force measurement example	
Figure 27	Acceptable foot insertion into stirrup-type step	50

Figure 28	Typical economy class step	50
Figure 29	Typical first/business class step	50
Figure 30	Seat description	55
Figure 31	Definition and determination of SRP	56
Figure 32	Evaluation object shape	
Table 1	Minimum passenger aisle width	15
Table 2	Injury potential analysis	24
Table 3	Maximum force values	41
Table 4	Mazard level evaluation lbf (N = newtons)	
Table 5	Examples of hazard modifying factor values	
Table 6	Hazard value and recommended actions	
Table 7	CAESAR anthropometric database sitting and standing height	
Table 8	Typical small parts	
Table 9	Seat secondary structure abuse loads	
Table 10	Seat secondary structure fatigue life	

1. SCOPE

This SAE Aerospace Recommended Practice (ARP) documents a common understanding of terms, compliance issues, and design criteria to facilitate certification of seat installations specific to Part 25 aircraft. This ARP provides general guidance for seats to be installed in Part 23 aircraft and Parts 27 and 29 rotorcraft and does not specify specific designs or design methods for such certification.

2. APPLICABLE DOCUMENTS

The following publications form a part of this document to the extent specified herein. The latest issue of SAE publications shall apply. The applicable issue of other publications shall be the issue in effect on the date of the purchase order. In the event of conflict between the text of this document and references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

AFRL-HE-WP-TR-2002-0170 CAESAR: Summary Statistics for the Adult Population (ages 18-65) of the United States

of America

AS5678 Passive RFID Tags Intended for Aircraft Use

AS8049 Performance Standard for Seats in Civil Rotorcraft, Transport Aircraft, and General

Aviation Aircraft

2.2 NAS Publications

Available from Aerospace Industries Association, 1000 Wilson Boulevard, Suite 1700, Arlington, VA 22209-3928, Tel: 703-358-1000, www.aia-aerospace.org.

NAS809 Specification - Aircraft Seats and Berths

2.3 CFR Publications

Available from the United States Government Printing Office, 732 North Capitol Street, NW, Washington, DC 20401, Tel: 202-512-1800, www.gpo.gov.

Code of Federal Regulations Title 14 Part 23 (14 CFR Part 23) Airworthiness Standards: Normal, Utility, and Acrobatic

Category Airplanes

Code of Federal Regulations Title 14 Part 25 (14 CFR Part 25) Airworthiness Standards: Transport Category Airplanes

Code of Federal Regulations Title 14 Part 27 (14 CFR Part 27) Airworthiness Standards: Normal Category Rotorcraft

Code of Federal Regulations Title 14 Part 29 (14 CFR Part 29) Airworthiness Standards: Transport Category Rotorcraft

Code of Federal Regulations Title 14 Part 121 (14 CFR 121) Certification and Operations: Domestic, Flag, and

Supplemental Air Carriers and Commercial Operators of Large Aircraft

2.4 FAA Publications

Available from Federal Aviation Administration, 800 Independence Avenue, SW, Washington, DC 20591, Tel: 866-835-5322, www.faa.gov.

AC 25-17A Transport Airplane Cabin Interiors Crashworthiness Handbook

AC 25.785-1B Flight Attendant Seat and Torso Restraint System Installations

PS-ANM100-2003-10019 Subject: Policy Statement on Evaluating a Seat Armrest Cavity for a Potential Fire Hazard

PS-ANM-25.853-01-R2 Subject: Flammability Testing of Interior Materials

ANM-04-115-28 Subject: Policy Statement on an Unreliable Design of Seat Belt Attachment, Fittings on

Passengers' Seats and Compliance with § 25.601

ANM-03-115-31 Policy Statement on Conducting Component Level Tests to Demonstrate Compliance with

§§ 25.785(b) and (d)

Special Airworthiness Information Bulletin (SAIB) NM-04-37, issued December 22, 2003, recommends that a specific design of seat belt attachment fitting be replaced with an improved design fitting.

2.5 Civil Aerospace Medical Institute

Available from the United States Government Printing Office, 732 North Capitol Street, NW, Washington, DC 20401, Tel: 202-512-1800, www.gpo.gov.

DOT/FAA/AM-03/9 Human Factors Associated with the Certification of Airplane Passenger Seats: Life

Preserver Retrieval

2.6 NASA Publications

NASA Technical Services, NASA STI Program STI Support Services, Mail Stop 148, NASA Langley Research Center, Hampton, VA 23681-2199, 757-864-9658, Fax: 757-864-6500, http://ntrs.nasa.gov/.

NASA-STD-3000 Vol. I Man Systems Integration Standards Rev. B, NASA Johnson Space Center, Houston, TX,

1995.

2.7 UL Publications

Available from UL, 333 Pfingsten Road, Northbrook, IL 60062-2096, Tel: 847-272-8800, www.ul.com.

UL 1439 Tests for Sharpness of Edges on Equipment

2.8 RTCA Publications

Available from RTCA, Inc., 1150 18th Street, NW, Suite 910, Washington, DC 20036, Tel: 202-833-9339, www.rtca.org.

DO-160G Environmental Conditions and Test Procedures for Airborne Equipment

3. RECOMMENDED PRACTICES

FAR references can be considered valid across aircraft categories: 14 Code of Federal Regulations Parts 23, 25, 27, and 29.

- 3.1 Seat Back Handhold in Turbulence
- 3.1.1 Applicable Policy and Regulations

14 CFR Part 25.785 (j) Amendment 25-88

If the seat backs do not provide a firm handhold, there must be a handgrip or rail along each aisle to enable persons to steady themselves while using aisles in moderately rough air.

AC 25-17A par. 81.b (6) Crashworthiness Handbook

The seat back may serve as a firm handhold. Since many seats are capable of breaking over, the breakover load must be adequate to be considered firm. A load of 25 pounds (111 N) minimum, acting horizontally, is considered adequate when applied at the top center of the seat back.

3.1.2 Recommended Practice

A handhold is defined as a means of providing a hand hold support for a person standing upright in an aisle during flight. If an adequate supplemental rail or handgrip is not provided in the interior, seat backs may be used as the handhold so long as they are spaced sufficiently close together to be within reach for an occupant using the aisle. For that purpose, a seat pitch of 65 inches (165 cm) or less is considered adequate in a typical commercial transport aircraft configured with forward or rearward facing passenger seats positioned along an aisle. Due to the unique and customized interior arrangement of forward, sideward, or rearward facing passenger seats in business/private transport aircraft (not for hire), these configurations should be assessed individually. Divan seating and side facing seats do not normally place the seat back where it can be effectively used as a handhold.

To act as a handhold, the upper aisle-side corner of the seat back should provide either a surface to grip or push against. A seat back used as a handhold should not break over when a force of 25 pounds (111 N) in a direction perpendicular to the seat back is applied at the top center of the seat back. Seat backs with head rests that telescope more than 3 inches (7.6 cm) above the seat back may be used for a handhold if, in addition to all other requirements, no portion of the head rest, e.g., bendable ears and/or tilting head rest, can be moved more than 7 inches (17.8 cm) before a 25 pound (111 N) resistive force is met.

The seat back handhold should be at least 33 inches (84 cm) above the floor, even if the seat back is reclined.

- 3.2 Seat Belt Misalignment/Disengagement
- 3.2.1 Applicable Policy and Regulations

14 CFR Part 25.601

General.

The airplane may not have design features or details that experience has shown to be hazardous or unreliable. The suitability of each questionable design detail and part must be established by tests.

14 CFR Part 25.562 Amendment 25-64

- (a) The seat and restraint system in the airplane must be designed as prescribed in this section to protect each occupant during an emergency landing condition when:
 - (1) Proper use is made of seats, safety belts, and shoulder harnesses provided for in the design.
 - (2) The occupant is exposed to loads resulting from the conditions prescribed in this section.

FAA Policy Memo ANM-04-115-28

Policy Statement on an Unreliable Design of Seat Belt Attachment Fittings on Passenger's Seats and Compliance with § 25.601.

This is a preview. Click here to purchase the full publication.